

EF2S-STD POWER UNIT

Part Number 71120E531050



SPECIFICATIONS

Length:	17.6 in.	(447 mm)
Width:	15.1 in.	(384 mm)
Height:	21.9 in.	(556 mm)
Weight (Ready-to-use)	112.7 lbs.	(51 kg)
(Includes hydraulic fluid and couplings)		
Fluid Type: AMKUS MV-1 Mineral Base Hydraulic Fluid		
Rated Output Pressure:	10,500 psi	(724 bar)
Hydraulic Fluid Reservoir Capacity:	2.0 gals. US	(7.6 liters)
Delivery of pump, stage 1:	1.20 gpm per port x 2	(4542 cc/min)
Delivery of pump, stage 2:	0.25 gpm per port x 2	(946 cc/min)

DESIGN & OPERATIONAL FEATURES

 Certified Model NFPA 1936, 2015 edition

- ★ Electric powered, 3.0 horsepower, “Washdown” motor
- ★ Two high pressure, two-stage pumping systems
- ★ Two 2-Way, 2-position selector valves
- ★ Two tools can be connected and operated simultaneously
- ★ Non-toxic mineral base hydraulic fluid
- ★ Carrying handle
- ★ Also available with roll cage
- ★ 220/240 Volt single phase



4201 Montdale Drive, Valparaiso, IN 46383
amkus.com • experts@amkus.com
800-592-6587 • 219-548-5000