

AMK-24 SPREADER

Part Number 320200001000



Optional Accessory:
Quick Adjust Chain Package
Part No. 391200001000



Optional Accessory:
Extended Reach Tip
Part No. 391000001010
Order (2) for a pair
(Increase the spread up to 8 in.)

SPECIFICATIONS

Maximum Spreader Opening:	24.0 in. (610 mm)
Maximum Spreader Travel Distance:	23.9 in. (607 mm)
Weight (Ready-to-use):	37.35 lbs. (17.0 kg)
Length:	29.7 in. (754 mm)
Width:	14.0 in. (356 mm)
Depth:	8.0 in. (203 mm)
Highest Spreading Force (NFPA 1936, HSF):	10,100 lbs. (44.8 kN)
Lowest Spreading Force (NFPA 1936, LSF):	9,145 lbs. (40.6 kN)
Highest Pulling Force (NFPA 1936, HPF):	6,218 lbs. (27.6 kN)
Lowest Pulling Force (NFPA 1936, LPF):	5,450 lbs. (24.2 kN)
Maximum Spreading Force (at back of tips):	18,785 lbs. (83.5 kN)
Rated Input Pressure:	10,500 psi (724 bar)
Spreader Opening Time:	4 seconds
Spreader Closing Time:	4 seconds

DESIGN & OPERATIONAL FEATURES

 *Certified Model NFPA 1936, 2015 edition*

 *EN13204 Designation: AS33/609-17.0*

- Unique construction allows maximum usable force
- Tips remain parallel to the cylinder throughout the spread allowing them to stay in contact with the material continuously for maximum spread (helps avoid piercing with the tips)
- Removable tips to accept chain package and optional tips for versatility
- Push button pins for easy removal of tips (eliminates possibility of losing pins in the field)
- Control valve placement provides compact design allowing greater access for the user
- Excellent balance and natural hand placement
- Anodized for corrosion protection

