

GH2A-MC MINI POWER UNIT

Part Number 701205516201



SPECIFICATIONS

Length:	19.0 in.	(482 mm)
Width:	17.0 in.	(432 mm)
Height:	17.8 in.	(452 mm)
Weight (Ready-to-use)	68.0 lbs.	(30.8 kg)
(Includes gas, engine oil, hydraulic fluid and couplings)		
Fluid Type: AMKUS MV-1 Mineral Base Hydraulic Fluid		
Rated Output Pressure:	10,500 psi	(724 bar)
Hydraulic Fluid Reservoir Capacity:	.68 gals. US	(2.57 liters)
Usable Hydraulic Fluid Capacity:	.66 gals. US	(2.50 liters)
Delivery of pump, stage 1:	0.8 gpm	(3028 cc/min)
Delivery of pump, stage 2:	0.14 gpm	(530 cc/min)

DESIGN & OPERATIONAL FEATURES

 *Certified Model NFPA 1936, 2015 edition*

 *EN13204 Designation: ATO*

- Gasoline powered 4 cycle Honda® engine
- Uses lead free gasoline
- Easy to fill with large fill port on reservoir
- Includes spark arresting muffler
- Non-toxic mineral base hydraulic fluid
- Two tools can be connected simultaneously
- High pressure, two-stage pumping system
- Alternate tool operation
- Roll cage for protection
- Easy access drain port to drain hydraulic fluid from pump



4201 Montdale Drive
Valparaiso, IN 46383-4098
219-548-5000
800-592-6587
Fax: 219-476-1669