AMKUS®
RESCUE SYSTEMS™
BUILT FOR THE MOMENT.
TRUSTED FOR A LIFETIME.
GRASSY POND
1381
FIREFIGHTER
YOUR POWER. YOUR CHOICE.
MADE IN THE USA

AMKUS
RESCUE SYSTEMS

BUILT FOR THE MOMENT.

For more than five decades, AMKUS has partnered with firefighters and rescue professionals to design tools that perform when lives are on the line. Proudly designed, manufactured, and assembled in the USA, every product is innovated with simplicity, durability, and reliability.

Everything we build has one purpose: helping you save lives faster, safer, and with confidence.

SIMPLE. Designed for intuitive operation under pressure.

RUGGED. Built to withstand the toughest environments.

RELIABLE. Trusted by departments worldwide.

Trusted by professional safety teams and training organizations nationwide.

NASCAR RESCUE SYSTEM SUPPLIER

NHRA OFFICIAL RESCUE TOOL

World of Outlaws

Interstate Batteries High Limit Racing

BuyBoard

eVA

HGACBuy

AMKUS Rescue Systems

@AMKUSRescueSystems

@AMKUSRescueSystems

@AMKUSRescueSystems

AMKUS Rescue Systems

Your Power. Your Choice.

Two trusted platforms. Built for firefighters.

Every department is different.
That's why AMKUS builds professional rescue tools
on both Milwaukee® and DeWalt® platforms—
so you can standardize your equipment
without changing what works.

Milwaukee®

DEWALT®

AMKUS® RESCUE SYSTEMS

AMKUS.COM

LIGHT RESCUE SERIES

Compact tools. Serious performance. Quiet operation.

Light Rescue Spreader

Lightweight spreading power for rapid, confident entry.

PART NUMBER: **LRS-MIL**

Length	34.2 in (869 mm)
Weight	43.8 lbs (19.8 kg)
Spreading Distance	29 in (737 mm)
Spreading Distance (with ERTs)	37 in (940 mm)
Highest Spreading Force (HSF)	9,640 lbs (43.7 kN)
Highest Pulling Force (HPF)	5,890 lbs (26.2 kN)
Maximum Theoretical Spreading Force	197,475 (895.7 kN)

Light Rescue Cutter

Lightning-fast cuts on today's toughest vehicle materials.

PART NUMBER: **LRC-MIL**

Length	32.3 in (820 mm)
Weight	46.6 lbs (21 kg)
Cutter Opening	6.2 in (160 mm)
Cutter Rating	A6/B8/C6/D7/E7/F4
Maximum Theoretical Cutting Force	259, 354 lbs (1,154 kN)

Light Rescue Combi

One tool. Two functions. Built for maximum versatility.

PART NUMBER: **LRCT-MIL**

Length	34.1 in (866 mm)
Weight	48.7 lbs (22 kg)
Spreading Distance	14 in (356 mm)
Spreading Distance (with ERTS)	21 in (533 mm)
Cutter Opening	11.9 in (302 mm)
Cutter Rating	A6/B6/C5/D6/E7/F4
Maximum Theoretical Spreading Force	273,097 lbs (1,215 kN)
Maximum Theoretical Cutting Force	102,067 (454 kN)

HEAVY RESCUE SERIES

Maximum force. Extended reach. Unmatched control.

Heavy Rescue Spreader

High-force spreading for heavy vehicles and complex entrapments.

PART NUMBER: **HRS-MIL**

Length	37 in (940 mm)
Weight	51.9 lbs (23 kg)
Spreading Distance	32 in (810 mm)
Spreading Distance (with ERTs)	40 in (933 mm)
Highest Spreading Force (HSF)	15,100 lbs (67 kN)
Lowest Spreading Force (LSF)	10,530 lbs (47 kN)
Highest Pulling Force (HPF)	11,500 lbs (51 kN)
Lowest Pulling Force (LPF)	7,580 lbs (34 kN)
Maximum Theoretical Spreading Force	197,783 lbs (880 kN)

Heavy Rescue Combi

Versatility and power in a single, all-purpose tool.

PART NUMBER: **HRCT-MIL**

Length	35 in (889 mm)
Weight	57.9 lbs (26 kg)
Spreading Distance	15.6 in (396 mm)
Spreading Distance (with ERTS)	23.6 in (599 mm)
Highest Spreading Force (HSF)	7,830 lbs (35 kN)
Cutter Opening	13.8 in (351 mm)
Cutter Rating	A7/B8/C7/D9/E8/F5
Maximum Theoretical Spreading Force	355,031 lbs (1,579 kN)
Maximum Theoretical Cutting Force	138,040 lbs (614 kN)

All tools have been 3rd party UL tested to NFPA 1960 Standards.

HEAVY RESCUE SERIES

Maximum force. Extended reach. Unmatched control.

Heavy Rescue Short Blade Cutter

Full-power cutting with shorter blades for tight, hard-to-reach access points.

PART NUMBER: **HRCS-MIL**

Length	31.5 in (800 mm)
Weight	52.9 lbs (24 kg)
Cutter Opening	5.8 in (147 mm)
Cutter Rating	A7/B8/C7/D9/E8/F4
Maximum Theoretical Cutting Force	350,762 lbs (1,560 kN)

Heavy Rescue Long Blade Cutter

Maximum cutting power for today's toughest, reinforced materials.

PART NUMBER: **HRCL-MIL**

Length	32.7 in (830 mm)
Weight	53.7 lbs (24 kg)
Cutter Opening	7 in (178 mm)
Cutter Rating	A8/B9/C7/D9/E9/F4
Maximum Theoretical Cutting Force	350,762 lbs (1,560 kN)

Heavy Rescue Telescoping Ram

Controlled, high-force pushing with rock-solid extension and stability.

PART NUMBER: **HRTR-MIL**

Length	22 in (559 mm)
Length Fully Extended	50.5 in (1,282 mm)
Weight	54 lbs (24 kg)
HSF Piston	48,540 lbs (216 kN)
HSF Piston	22,390 (100 kN)

LIGHT RESCUE SERIES

Lightweight design. Powerful capability. Fast when it counts.

Light Rescue Spreader

Lightweight spreading power that saves lives faster.

PART NUMBER: **LRS**

Length	35.2 in (894 mm)
Weight	43.2 lbs (19.5 kg)
Spreading Distance	29 in (737 mm)
Spreading Distance (with ERTs)	37 in (940 mm)
Highest Spreading Force (HSF)	9,640 lbs (43.7 kN)
Highest Pulling Force (HPF)	5,890 lbs (26.2 kN)
Maximum Theoretical Spreading Force	197,475 (895.7 kN)

Light Rescue Cutter

Reliable, high-performance cutting on modern vehicle materials.

PART NUMBER: **LRC**

Length	33.6 in (853 mm)
Weight	46 lbs (21 kg)
Cutter Opening	6.3 in (160 mm)
Cutter Rating	A6/B8/C6/D7/E7/F4
Maximum Theoretical Cutting Force	259, 354 lbs (1,154 kN)

Light Rescue Combi

Versatile spread-and-cut capability in one dependable tool.

PART NUMBER: **LRCT**

Length	35.3 in (897 mm)
Weight	47.9 lbs (22 kg)
Spreading Distance	14 in (356 mm)
Spreading Distance (with ERTS)	21 in (533 mm)
Cutter Opening	11.9 in (302 mm)
Cutter Rating	A6/B6/C5/D6/E7/F4
Maximum Theoretical Spreading Force	273,097 lbs (1,215 kN)
Maximum Theoretical Cutting Force	102,067 (454 kN)

All tools have been 3rd party UL tested to NFPA 1960 Standards.

Heavy Rescue Spreader

Serious spreading power for demanding, complex extrications.

PART NUMBER: **HRS**

Length	37.9 in (963 mm)
Weight	51.4 lbs (23 kg)
Spreading Distance	32 in (810 mm)
Spreading Distance (with ERTs)	40 in (933 mm)
Highest Spreading Force (HSF)	15,100 lbs (67 kN)
Lowest Spreading Force (LSF)	10,530 lbs (47 kN)
Highest Pulling Force (HPF)	11,500 lbs (51 kN)
Lowest Pulling Force (LPF)	7,580 lbs (34 kN)
Maximum Theoretical Spreading Force	197,783 lbs (880 kN)

Heavy Rescue Combi

All-in-one versatility backed by dependable heavy-duty performance.

PART NUMBER: **HRCT**

Length	35.9 in (914 mm)
Weight	57.4 lbs (26 kg)
Spreading Distance	15.6 in (396 mm)
Spreading Distance (with ERTS)	23.6 in (599 mm)
Highest Spreading Force (HSF)	7,830 lbs (35 kN)
Cutter Opening	13.8 in (351 mm)
Cutter Rating	A7/B8/C7/D9/E8/F5
Maximum Theoretical Spreading Force	355,031 lbs (1,579 kN)
Maximum Theoretical Cutting Force	138,040 lbs (614 kN)

Heavy Rescue Short Blade Cutter

Full-power cutting with shorter blades for confined access points.

PART NUMBER: **HRCS**

Length	32.5 in (826 mm)
Weight	52.5 lbs (24 kg)
Cutter Opening	5.8 in (147 mm)
Cutter Rating	A7/B8/C7/D9/E8/F4
Maximum Theoretical Cutting Force	350,762 lbs (1,560 kN)

Heavy Rescue Long Blade Cutter

Serious cutting power for reinforced and high-strength materials.

PART NUMBER: **HRCL**

Length	33.4 in (856 mm)
Weight	53.1 lbs (24 kg)
Cutter Opening	7 in (178 mm)
Cutter Rating	A8/B9/C7/D9/E9/F4
Maximum Theoretical Cutting Force	350,762 lbs (1,560 kN)

Heavy Rescue Telescoping Ram

Controlled, high-force pushing with rock-solid extension and stability.

PART NUMBER: **HRTR**

Length	22.1 in (561 mm)
Length Fully Extended	50.5 in (1,282 mm)
Weight	53.3 lbs (24 kg)
HSF Piston 1	48,540 lbs (216 kN)
HSF Piston 2	22,390 (100 kN)

All tools have been 3rd party UL tested to NFPA 1960 Standards.

Extend Your Reach

Versatility for your Spreader and Combi tools

Extended Reach Tips (ERTs) are built exclusively for AMKUS spreader and combi tools.

- Increases spread up to 8 inches to quickly access and stabilize in complex entrapments
- Allows for up to 16 different configurations to adapt your tool to meet the demands of the scene
- Optimized for both the DeWalt and Milwaukee battery platforms

Spreader Extended Reach Tips (ERTs)

Combi Extended Reach Tips (ERTs)

Tip Gator Grip

Power Your System

Batteries, chargers, and accessories built for your Milwaukee and DeWalt tools.

AMKUS offers a complete selection of batteries, chargers, and compatible accessories for both Milwaukee® and DeWalt® powered tools.

Batteries & Chargers

Available in multiple capacities and configurations.

FOR THE FULL LINEUP—INCLUDING SPECIALTY KITS AND HAND TOOLS—VISIT AMKUS.COM.

Line Tools Available

Is your department still operating with line tools? AMKUS continues to support departments using traditional hydraulic systems. All Light Rescue and Heavy Rescue Series tools are available in line tool configurations—delivering the same Simple. Rugged. Reliable. performance trusted in the field.

BUILT FOR THE MOMENT.

TRUSTED FOR A LIFETIME.

AMKUS®
RESCUE SYSTEMS™

3701 Innovation Way
Valparaiso, IN 46383
800-592-6587
experts@amkus.com
amkus.com

Milwaukee® and DeWalt® Powered Rescue Systems
Proudly Designed, Manufactured, and Assembled in the USA

AMKUS Rescue Systems reserves the right to make changes in design and specifications without notice.

© Copyright AMKUS Rescue Systems 2026